

Paving Breakers and Chipping Hammers



Engineered to last

mac³

Paving Breakers

POWER and RELIABILITY for all medium and heavy duty demolition works in the construction sector.



BB32



BB40
with muffler

Vibro-reduced breakers

Reducing vibration impact on the operator has become a key health issue in some areas.

MAC3 vibro-reduced breakers have an equivalent impact power as a standard breaker, while significantly reducing vibrations to the operator.



BB25
vibro-reduced

Standard paving breakers

Standard breakers are available either in a basic version or in a silenced version with a slim design muffler offering a full view of the work surface while significantly reducing noise. The muffler can also be supplied in kit to be added later on a standard breaker.

Breakers with enhanced ergonomic design

MAC3 has created solutions for optimal comfort of use in parallel with improved hammer operation safety. The aim is to prevent risks of injuries to the user and to limit his exposure to workplace accidents.



★ **Hands protection:** for better safety at work, in particular in trenches, we have added hand protections to prevent damages to operator's fingers while maintaining easy breaker handling.

★ **Safety trigger:** to prevent from accidental action of a breaker and putting the operator in danger, MAC3 has designed a double safety control.

| Model | Muffler (1) | Vibro-reduced | Hands protection | Safety device (1) | Weight | | Length | | Impact rate | Air consumption | | Shank size | | |
|-------|-------------|---------------|------------------|-------------------|--------|----|--------|------|-------------|-----------------|------|------------|----------|---------------|
| | | | | | kg | lb | mm | in. | | l/s | cfm | Type | mm | in. |
| BB15 | o | na | o | o | 16 | 35 | 580 | 22.8 | 1 600 | 17.5 | 37.1 | Hex | 22 x 82 | 7/8" x 3 1/4" |
| BB15 | o | na | o | o | 18 | 40 | 620 | 24.4 | 1 600 | 17.5 | 37.1 | Hex | 25 x 108 | 1" x 4 1/4" |
| BB20 | • | • | na | o | 20.9 | 46 | 660 | 26.0 | 1 300 | 18.3 | 38.8 | Hex | 25 x 108 | 1" x 4 1/4" |
| BB25 | • | • | na | o | 24.2 | 53 | 718 | 28.3 | 1 300 | 20 | 42.4 | Hex | 28 x 160 | 1 1/8" x 6" |
| BB25 | • | • | na | o | 24.2 | 53 | 718 | 28.3 | 1 300 | 20 | 42.4 | Hex | 32 x 160 | 1 1/4" x 6" |
| BB32 | o | na | o | o | 32 | 71 | 690 | 27.2 | 1 350 | 27.5 | 58.3 | Hex | 28 x 160 | 1 1/8" x 6" |
| BB32 | o | na | o | o | 32 | 71 | 690 | 27.2 | 1 350 | 27.5 | 58.3 | Hex | 32 x 160 | 1 1/4" x 6" |
| BB40 | o | na | o | o | 38 | 84 | 705 | 27.8 | 1 280 | 30 | 63.6 | Hex | 28 x 160 | 1 1/8" x 6" |
| BB40 | o | na | o | o | 38 | 84 | 705 | 27.8 | 1 280 | 30 | 63.6 | Hex | 32 x 160 | 1 1/4" x 6" |

• = standard ; o = option ; na = not applicable ; (1) = mandatory in countries requiring EC-marking